Accessories for the distribution network

Splitters

EBC 10 272859
EBC 13 21610004
EBC 14 21610005

- Frequency range: 5-2,400 MHz
- Remote feed suitable: max. 24 V; 0.5 A (via all outputs, e.g. for signal distribution in one-cable systems with the UAS 481 one-cable quatro feed system)
- Integrated decoupling diodes, current flow direction: OUT → IN
- Connections: F connectors
- Connection for potential equalisation
- Small dimensions
- Conform to: EN 60728-11 and EN 50083-2
- For indoor mounting

EBC 10

EBC 13

EBC 14

			2-way	3-way	4-way
Type			**EBC 10**	**EBC 13**	**EBC 14**
Order no.			272859	21610004	21610005
Through loss	5-47 MHz 47-862 MHz 862-2,150 MHz 2,150-2,400 MHz	dB	4 5 6 8	8 8 10.5 12	11 10 11.5 13.5
Decoupling	5-47 MHz 47-862 MHz 862-2,150 MHz 2,150-2,400 MHz	dB	10 20 20-15 10	10 20 20-15 10	10 20 20-15 10
Screening factor	5-300 MHz 300-470 MHz 470-950 MHz 950-2,400 MHz	dB	> 85 > 80 > 75 > 55		
Dimensions		mm	55 x 52 x 23	55 x 52 x 23	55 x 74 x 23
Packing unit/weight		pc./kg	1 (10, 200)/0.1	1 (10, 200)/0.1	1 (10, 160)/0.1